



EXPAND TOUR RANGE OF
APPLICATIONS WITH THE
IG SERIES
OF DIGITAL PLATFORM
SCALES

IG

SERIES

SPECIFICATION



Model	IGB-30	IGB-60/IGB-150	IGX-30	IGX-60/IGX-150
Max Weighing Capacity	30kg	60kg / 150 kg	30kg	60kg / 150 kg
Platter Material	Stainless Steel			
Platter Size (Length x Width)	380mm x 380 mm	550 mm x 400 mm	380 mm x 380 mm	550 mm x 400 mm
Min Graduation	10 g	20g / 50 g	10g	20 g / 50 g
Accuracy	1/30000, 1/60000, 1/75000			
Display	LCD		VFP*	
Display Annunciators	Weight 5 digit with 7 On/Indication Lights: Stable, Zero, Tare, Upper Limit, Lower Limit, Weight OK, Low Battery		Weight 5 digit with 6 Indication Lights: Stable, Zero, Tare, Upper Limit, Lower Limit, Weight OK	
Measuring System	2 D-Size Batteries (500 Operating Hours) or AC Adaptor		Load Cell	
Power Supply	0.2W		AC220 / 50 Hz	
Power Consumption	-10°C - +40 °C			
Operating Temperature	7W			
Operating Humidity	15%RH ~ 85% RH			
Weight	8.5 kg	19kg	8.5kg	19kg
Others	Auto Turn Off Function			

SIMPLE TO USE TARE FUNCTION

Place a container on the platform and press the Tare key. The tare is automatically stored in memory and the net weight is displayed during each subsequent weighing.

IG

SERIES

EASY-TO-READ, ROTATING DISPLAY
Choose a large bright VFD display or a wide LCD display to meet your application needs and ease operator reliability. For optimum viewing, and to help eliminate errors, the indicator head can be vertically adjusted with the turn knobs.

CHECK WEIGHING FUNCTION SIMPLIFIES CONTROL
When the user defined upper limit is exceeded, the letter "H" is displayed. When the value is under the lower limit, "L" is displayed. An audible beep warns the operator that item is out of tolerance.

AUTO POWER OFF FUNCTION

The IGB model features battery operation with a selectable automatic power-off function (10, 20, 30, 40, 50, 60 minutes or off) to extend battery life. For those applications where AC power is available select either the IGB with optional AC adaptor or IGX.